



CTS ELECTRONIC COMPONENTS SA

Erlenstrasse 31, 2555 Brügg, Switzerland - Phone +41 32 366 50 50 - Fax +41 32 366 50 59 - E-mail fordahl@fordahl.ch

DEV	TCXO - FREQUENCY THERMAL STABILITIES AVAILABLE OVER OPERATING TEMPERATURE RANGES	Date: 17.05.2011	Visa: MYP
-----	--	------------------	-----------

This table concerns the TCXO products : DFA S2, DFA S1, DFA 14-C and DFA S4.

The multiplied versions DFA S1-M and DFA S4-M are not concerned by this document.

Operating Temperature Ranges	Frequency Stabilities vs Operating Temperature Ranges			
	5 to 20 MHz	20.1 to 25 MHz	25.1 to 35 MHz	35.1 to 52 MHz
0°C to 50°C	± 0.28 ppm *	± 0.8 ppm	± 1.5 ppm	± 2.0 ppm
0°C to 70°C	± 0.28 ppm *	± 0.8 ppm	± 1.5 ppm	± 2.0 ppm
-20°C to 70°C	± 0.28 ppm *	± 0.8 ppm	± 1.5 ppm	± 2.0 ppm
-30°C to 75°C	± 0.28 ppm *	± 1.0 ppm	± 1.5 ppm	± 2.0 ppm
-40°C to 85°C	± 0.28 ppm *	± 1.0 ppm	± 1.5 ppm	± 2.0 ppm

* Not available for all frequencies, please consult factory.