

SURFACE MOUNT TCXO WITH INTERNAL TRIMMER

DFA S1-KHAZ (5 V) & DFA S1-LHAZ (3.3 V)

KEY FEATURES




5 to 52 MHz

HCMOS output, Tight stability

Analogue temperature compensation

APPLICATIONS

Transmissions, SDH/Sonet, Microwave



PC board footprint

Function	DFA S1
NC	1
E / D	2
GND	3
Output	4
NC	5
Vcc	6

TYPE	DFA S1-KHAZ	DFA S1-LHAZ
Frequency Range	5 to 52 MHz	

ELECTRICAL SPECIFICATIONS	DFA S1-KHAZ	DFA S1-LHAZ
supply voltage	5 V ± 5 %	3.3 V ± 5 %
supply current (no load)	≤ 20 mA	≤ 10 mA
output load	HCMOS 15 pF or 2 TTL	HCMOS 15 pF or 2 TTL
duty cycle @ 50% level	45/55...55/45 %	45/55...55/45 %
rise/fall times (10 to 90 %)	≤ 5 ns	≤ 5 ns
high/low levels or output amplitude	≥ 4.5 V / ≤ 0.5 V	≥ 2.8 V / ≤ 0.3 V
start-up	≤ 10 ms @ 4.75 V	≤ 10 ms @ 3.15 V
tri-state control on pin 2	high or open = enable, low = high Z	high or open = enable, low = high Z

FREQUENCY STABILITY			detailed tolerances [ppm]			
type	temperature range	model code	stability versus:			calibration @ 25°C
			temperature	Vcc ± 5 %	load ± 10 %	
all types	0 to 70 °C	B0.5*	≤ ± 0.5	≤ ± 0.1	≤ ± 0.1	≤ ± 1
	-20 to 70 °C	C0.5*	≤ ± 0.5			
	-20 to 70 °C	C1*	≤ ± 1.0			
	-40 to 85 °C	E1*	≤ ± 1.0			
	-40 to 85 °C	E2	≤ ± 2.0			
remarks			* Not available at all frequencies, please consult factory for more details			
Internal trimmer			ageing is 1 st year at 25 °C			
			pulling ≥ ± 5 ppm			

ORDERING CODE	type + option code + frequency + model code
Example	DFA S1-LHAZ 12.8 MHz E1