


SURFACE MOUNT TCXO

DFA S7-CH (5 V) & DFA S7-CLH (3.3 V)

KEY FEATURES
5 to 52 MHz Tight temperature stability Analogue temperature compensation
APPLICATIONS
Transmissions, SDH/Sonet, Microwave

Function	DFA S7
NC / V control	1
GND	2
Output	3
Vcc	4



TYPE	DFA S7-CH	DFA S7-CLH
Frequency Range	5 to 52 MHz	

ELECTRICAL SPECIFICATIONS	DFA S7-CH	DFA S7-CLH
supply voltage	5 V ± 5 %	3.3 V ± 5 %
supply current (no load)	≤ 20 mA	≤ 10 mA
output load	HCMOS 15 pF or 2 TTL	HCMOS 15 pF or 2 TTL
duty cycle @ 50% level	45/55...55/45 %	45/55...55/45 %
rise/fall times (10 to 90 %)	≤ 5 ns	≤ 5 ns
high/low levels or output amplitude	≥ 4.5 V / ≤ 0.5 V	≥ 2.8 V / ≤ 0.3 V
start-up	≤ 10 ms @ 4.75 V	≤ 10 ms @ 3.15 V

FREQUENCY STABILITY			detailed tolerances [ppm]			
type	temperature range	model code	temperature	stability versus:		calibration @ 25°C
				Vcc ± 5 %	load ± 10 %	
all types	0 to 70 °C	B0.5*	≤ ± 0.5	≤ ± 0.1	≤ ± 0.1	≤ ± 1
	-20 to 70 °C	C0.5*	≤ ± 0.5			
	-40 to 85 °C	E0.5*	≤ ± 0.5			
	-40 to 85 °C	E1*	≤ ± 1.0			
	-40 to 85 °C	E2	≤ ± 2.0			
remarks			* Not available at all frequencies, please consult factory for more details ageing is 1 st year at 25°C			

OPTIONS	CODE	DFA S7-CH	DFA S7-CLH
voltage control on pin 1 (positive slope)	V	≥ ± 5 ppm, ≤ ± 15 ppm 2.5 V ± 2 V	≥ ± 5 ppm, ≤ ± 15 ppm 1.65 V ± 1.35 V

ORDERING CODE	type + option code + frequency + model code
Examples	DFA S7-CLHV 20 MHz E0.5